



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
09/514,608	02/28/2000	Pantelis Monogioudis	7-23-2	9279

7590 04/08/2004

Docket Administrator  
Lucent Technologies Inc  
600 Mountain Avenue  
PO Box 636  
Murray Hill, NJ 07974-0636

EXAMINER

CORSARO, NICK

ART UNIT	PAPER NUMBER
----------	--------------

2684

DATE MAILED: 04/08/2004

Please find below and/or attached an Office communication concerning this application or proceeding.

# Office Action Summary

Application No.

09/514,608

Applicant(s)

MONOGIUDIS ET AL.

Examiner

Nick Corsaro

Art Unit

2684

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

## Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTH(S) FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If the period for reply specified above is less than thirty (30) days, a reply within the statutory minimum of thirty (30) days will be considered timely.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

## Status

- 1) ☒ Responsive to communication(s) filed on 23 February 2004.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

## Disposition of Claims

- 4) ☒ Claim(s) 1,2,4,6-17,19-25,28-38 and 40-43 is/are pending in the application.
- 4a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 5) ☒ Claim(s) 34-37 is/are allowed.
- 6) ☐ Claim(s) 1,2,4,6-8,10-15,17,19-25,28-33,38 and 40-43 is/are rejected.
- 7) ☒ Claim(s) 9 and 16 is/are objected to.
- 8) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

## Application Papers

- 9) ☐ The specification is objected to by the Examiner.
- 10) ☐ The drawing(s) filed on \_\_\_\_\_ is/are: a) ☐ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).
- 11) ☐ The oath or declaration is objected to by the Examiner. Note the attached Office Action or form PTO-152.

## Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).
- a) ☐ All b) ☐ Some \* c) ☐ None of:
- ☐ Certified copies of the priority documents have been received.
  - ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  - ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).
- \* See the attached detailed Office action for a list of the certified copies not received.

## Attachment(s)

- ☐ Notice of References Cited (PTO-892)
- ☐ Notice of Draftsperson's Patent Drawing Review (PTO-948)
- ☒ Information Disclosure Statement(s) (PTO-1449 or PTO/SB/08)  
Paper No(s)/Mail Date 7.
- ☐ Interview Summary (PTO-413)  
Paper No(s)/Mail Date. \_\_\_\_\_.
- ☐ Notice of Informal Patent Application (PTO-152)
- ☐ Other: \_\_\_\_\_.

## RESPONSE TO AMENDMEN

### *Response to Arguments*

1. Applicant's arguments filed 02/23/2004 have been fully considered but they are not persuasive.

The applicants features in the claims wherein a method and system in communications system includes, determining a signature of a communication channel wherein the signature of the communications channel is a second order statistic of a signal to noise ratio of a signal received from the communications channel; performing power control over the communications channel wherein the power control compares the metric value and a target metric value, such that a target metric value is adjusted as a function of the determined signature of the communication channel, reads upon Kanai in view of Minde as follows.

Kanai is discussing a transmission power control technique wherein signal quality in the communication environment is kept constant. Kanai discusses determining a characteristic of the communication channel by doing a first order statistic or averaging of a channel quality measurement and adjusting a power control target value. Therefore, Kanai, is disclosing the general structure of the applicants invention in that Kanai is adjusting the target value for power control based on a check of the communication channel. Kanai did not specifically disclose doing a second order statistic of a SNR. Minde showed doing a second order statistic of an SNR. Minde discussed methods to determine radio link parameters where Minde showed that a second order statistic, i.e., a standard deviation, of a SNR could be used to characterize the signature of a communication channel. Kanai was modified by Minde to show it is obvious to one of ordinary skill in the art to do the second order statistic of the communication channel to

Art Unit: 2684

determine the signature. Kanai and Minde were modified by Wang and Dohi to show look up tables, symbol error counts and changing the target SNR values.

In response to the applicants' arguments that the combination of Kanai and Minde is not proper to produce the invention, the arguments are not persuasive in that Kanai is already checking channel quality using Bit Error rate (BER), where Minde shows checking channel quality using BER and a second order statistic of BER, or substituting the SNR for the BER.

Therefore, the argued features are written broad such that they read upon the cited references.

***Claim Rejections - 35 USC § 103***

2. The following is a quotation of 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102 of this title, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

3. Claims 1, 2, 4, 6, 11-13, 17, 19-20, 23-25, 29, 31, 38, 40, and 43, are rejected under 35 U.S.C. 103(a) as being unpatentable over Kanai et al. (5,386,589) in view of Minde et al. (6,201,960).

Consider claim 1, Kanai discloses a method for use in a communications endpoint (see col. 1 lines 55-68 and col. 2 lines 1-5, where Kanai is discussing power control of transmit terminals by receiver terminals, i.e., endpoints, in a cellular communication system). Kanai discloses determining a parameter of a communications channel (see col. 7 lines 16-25). Kanai discloses performing power control over the communications channel wherein the power control compares a metric value and a target metric value (see col. 7 lines 47-68, col. 8 lines 54-68, and

Art Unit: 2684

col. 9 lines 1-13). Kanai discloses that the target metric value is adjusted as a function of the determined parameter of the communications channel (see col. 8 lines 15-55).

Kanai discloses determining a parameter of the communication channel by averaging, where logically the signal can be evaluated by other statistical methods to develop a signature (see col. 8 lines 15-68), however, Kanai does not specifically disclose a signature of communication channel, wherein the signature of the communication channel is a second order statistic of a signal to noise ration of the signal received from the communication channel.

Minde teaches a signature of the communication channel wherein the signature of the communication channel is a second order statistic of a signal to noise ration of the signal received from the communication channel (see col. 2 lines 60-67, col. 3 lines 1-17, and col. 4 lines 20-67, col. 5 lines 62-67).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the invention of Kanai, and have a signature of the communication channel, wherein the signature of the communication channel is a second order statistic of a signal to noise ration of the signal received from the communication channel as taught by Minde, thus allowing the system to account for fast fading, as discussed by Minde (col. 2 lines 14-60).

Consider claim 11, Kanai discloses a method for use in a communications endpoint (see col. 1 lines 55-68 and col. 2 lines 1-5, where Kanai is discussing power control of transmit terminals by receiver terminals, i.e., endpoints in a cellular communication system). Kanai discloses receiving a signal from a wireless endpoint; developing a statistic from the received signal; and performing power control with the wireless endpoint as a function of the second order statistic (see col. 8 lines 25-68, col. 9 lines 1-13, lines 57-68, and col. 7 lines 47-69).

Kanai discloses taking an average of the Bit Error Rate, i.e., a statistic (see col. 8 lines 54-67), however does not specifically disclose a second order statistic, from the received signal based on a signal to noise ration of the received signal. Minde teaches a second order statistic, from the received signal based on a signal to noise ration of the received signal (see col. 2 lines 60-67, col. 3 lines 1-17, and col. 4 lines 20-67, col. 5 lines 62-67 col. 4 lines 20-42).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the invention of Kanai, and a second order statistic from the received signal based on a signal to noise ration of the received signal, as taught by Minde, thus allowing the system to account for fast fading, as discussed by Minde (col. 2 lines 14-60).

Consider claim 17, Kanai discloses a method for use in a communications endpoint (see col. 1 lines 55-68 and col. 2 lines 1-5, where Kanai is discussing power control of transmit terminals by receiver terminals, i.e., endpoints in a cellular communication system). Kanai discloses the method comprising the steps of measuring a parameter of a fading environment (see col. 1 lines 49-55, col. 6 lines 23-30, col. 8 lines 25-68). Kanai discloses performing power control by adjusting a target metric value as a function of the measured signature (see col. 8 lines 25-68, col. 9 lines 1-14, lines 57-68, and col. 7 lines 47-69).

Kanai discloses determining a parameter of the communication channel by averaging, where logically the signal can be evaluated by other statistical methods to develop a signature (see col. 8 lines 15-68), however, Kanai does not specifically disclose a signature of communication channel, wherein the measuring includes calculating a standard deviation value of a signal to noise ratio of a received signal. Minde teaches a signature of the communication channel, wherein the measuring includes calculating a standard deviation value of a signal to

Art Unit: 2684

noise ratio of a received signal (see col. 5 lines 62-67 col. 2 lines 60-67, col. 3 lines 1-17, and col. 4 lines 20-67).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the invention of Kanai, and have a signature of the communication channel, wherein the measuring includes calculating a standard deviation value of a signal to noise ratio of a received signal, as taught by Minde, thus allowing the system to account for fast fading, as discussed by Minde (col. 2 lines 14-60).

Consider claim 24, Kanai discloses an apparatus for use in a communication endpoint (see col. 1 lines 55-68 and col. 2 lines 1-5, where Kanai is discussing power control of transmit terminals by receiver terminals, i.e., endpoints in a cellular communication system). Kanai discloses a receiver for receiving a signal, a controller for (a) developing a parameter of the communications channel from the received signal (see col. 1 lines 49-55, col. 6 lines 23-30, col. 8 lines 25-68). Kanai discloses performing power control over the communications channel by adjusting a target metric value as a function of the parameter of the communications channel (see col. 8 lines 25-68, col. 9 lines 1-14, lines 57-68, and col. 7 lines 47-69).

Kanai discloses determining a parameter of the communication channel by averaging, where logically the signal can be evaluated by other statistical methods to develop a signature (see col. 8 lines 15-68), however, Kanai does not specifically disclose a signature of communication channel, wherein the controller further determines the signature of the communication channel by collecting signal to noise ratio values of the received signal and by calculating a second order statistic of the collected signal to noise ratio values. Minde teaches a signature of the communication channel, wherein the controller further determines the signature

Art Unit: 2684

of the communication channel by collecting signal to noise ratio values of the received signal and by calculating a second order statistic of the collected signal to noise ratio values (see col. 5 lines 62-67, col. 2 lines 60-67, col. 3 lines 1-17, and col. 4 lines 20-67).

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the invention of Kanai, and have a signature of the communication channel, wherein the controller further determines the signature of the communication channel by collecting signal to noise ratio values of the received signal and by calculating a second order statistic of the collected signal to noise ratio values, as taught by Minde, thus allowing the system to account for fast fading, as discussed by Minde (col. 2 lines 14-60).

Consider claim 38, Kanai discloses an apparatus for use in equipment for providing power control in a cellular system (see col. 4 lines 63-68). Kanai discloses a receiver for receiving a signal from a wireless endpoint (see col. 5 lines 30-67). Kanai discloses a controller for (a) developing a statistic from the received signal wherein said statistic is used to determine an adjustment to a target metric value; and (b) performing power control with the wireless endpoint as a function of the statistic (see col. 8, lines 25-68, col. 9 lines 1-13, col. 2 lines 57-68, and col. 7 lines 47-69).

Kanai discloses taking an average of the Bit Error Rate (see col. 8 lines 54-67), however does not specifically disclose a second order statistic, wherein the controller calculates the second order statistic of collected signal to noise ratio values of the received signal. Minde teaches a second order statistic, wherein the controller calculates the second order statistic of collected signal to noise ratio values of the received signal (see col. 4 lines 20-67 and col. 5 lines 62-67).



Art Unit: 2684

It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the invention of Kanai, and a second order statistic wherein the controller calculates the second order statistic of collected signal to noise ratio values of the received signal, as taught by Minde, thus allowing the system to account for fast fading, as discussed by Minde (col. 2 lines 14-60).

Consider claims 2, 20, and 25, Kanai discloses the metric is a bit error rate (BER) (see col. 8 lines 54-67 and col. 9 lines 1-13).

Consider claim 19, Kanai discloses the parameter of the channel includes an average bit error rate (BER) and signal power or carrier interference ratio (CIR), where the average is a statistic (see col. 2 lines 5-68), however, does not specifically disclose a signature of the communications channel where the signature is a second order statistic of a received signal-to-noise ratio (SNR). Minde teaches a signature of the communications channel where the signature is a second order statistic of a received signal-to-noise ratio (SNR) (see col. 4 lines 20-67 and col. 5 lines 62-67). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the invention of Kanai, and have a signature of the communications channel where the signature is a second order statistic of a received signal-to-noise ratio (SNR), as taught by Minde, thus allowing the system to account for fast fading, as discussed by Minde (col. 2 lines 14-60).

Consider claims 4, and 29, Kanai does not specifically disclose collecting signal-to-noise (SNR) values of a signal received from the communications channel; and using the collected SNR values to determine the signature of the communications channel. Minde teaches collecting signal-to-noise (SNR) values of a signal received from the communications channel; and using

Art Unit: 2684

the collected SNR values to determine the signature of the communications channel (col. 4 lines 20-67 and col. 5 lines 62-67). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the invention of Kanai, and collect signal-to-noise (SNR) values of a signal received from the communications channel; and use the collected SNR values to determine the signature of the communications channel, as taught by Minde, thus allowing the system to account for fast fading, as discussed by Minde (col. 2 lines 14-60).

Consider claims 6, 23, and 31, Kanai discloses the communications endpoint is a wireless endpoint (see col. 1 lines 55-67).

Consider claim 12, Kanai discloses calculating a statistic of a bit error rate of the received signal; and adjusting a bit error rate target value as a function of the calculated statistic; and the performing step includes the step of performing reverse-link outer loop power control as a function of a comparison between a bit error rate value of the received signal and the adjusted bit error rate target value (see col. 8 lines 15-68 and col. 9 lines 1-14, where Kanai is discussing resetting the system target values to perform reverse power control, therefore, by definition Kanai is performing reverse outer loop power control). Kanai does not specifically disclose calculating a second order. Minde teaches calculating a second order statistic (see col. 4 lines 20-55 and col. 5 lines 60-67). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the invention of Kanai, and calculating a second order statistic, as taught by Minde, thus allowing the system to account for fast fading, as discussed by Minde (col. 2 lines 14-60).

Consider claim 13, Kanai discloses the communications endpoint is a wireless endpoint (see col. 1 lines 55-67).

Consider claim 40, Kanai discloses the metric is a bit error rate (BER) (see col. 8 lines 54-67 and col. 9 lines 1-13).

Consider claim 43, Kanai discloses a transmitter for transmitting power control information to the mobile (see col. 7 lines 48-68).

4. Claims 7-8, 10, 14-15, 28, 32-33, 41, and 42 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kanai in view of Minde as applied to claims 1, 11, 24, and 38 above, and further in view of Wang et al. (6,084,904).

Consider claims 7, 10, 14, 32, and 41 Kanai and Minde do not specifically disclose the metric is a symbol error count. Wang teaches the metric is a symbol error count (see col. 7 lines 9-20, col. 5 lines 67, and col. 6 lines 1-15). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the invention of Kanai and Minde, and have the metric be a symbol error count in outer loop power control, as taught by Wang, thus allowing a decrease in time over which threshold adjustments occur, as discussed by Wang (col. 2 lines 20-25).

Consider claims 8, 15, 33, and 42 Kanai, discloses the method as modified by Minde, wherein the determining step includes the step of monitoring an bit error count of a received signal for determining a standard deviation of the received bit error count; and the performing step includes the step of adjusting a target bit error count for the received signal as a function of the standard deviation for use in providing the power control (see Kanai col. 8 lines 15-68, col. 9 lines 1-47, and Minde col. 4 lines 20-43, where Kanai is discussing measuring the signal quality and Minde is discussing more accurately measuring the signal quality by higher order statistical methods). Kanai and Minde do not specifically disclose a symbol error count. Wang teaches a

Art Unit: 2684

symbol error count (see col. 7 lines 9-20, col. 5 lines 67, and col. 6 lines 1-15). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the invention of Kanai and Minde, and have the metric be a symbol error count in outer loop power control, as taught by Wang, thus allowing a decrease in time over which threshold adjustments occur, as discussed by Wang (col. 2 lines 20-25).

Consider claim 28, Kanai discloses the method and apparatus, as modified by Minde, wherein second order statistics are used via processors with inherent memories for determining the statistics (see Minde col. 4 lines 5-68). Kanai and Minde do not specifically disclose using tables. Official notice is taken that both the concept and advantage of using look up tables for mapping statistical values rather than calculating all values are well known and expected in the art. It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the invention of Kanai and Minde, and use look up tables to map the statistical values, thereby speeding up calculation by having some of the values previously stored for lookup.

5. Claims 21, 22, and 30 are rejected under 35 U.S.C. 103(a) as being unpatentable over Kanai in view of Minde as applied to claim 17 and 24, above, and further in view of Dohi et al. (6,341,224).

Consider claims 21, 22, and 30, Kanai discloses the method and apparatus, as modified by Minde above, wherein BER rate is measured and target values are changed such as BER or SNR. Kanai and mind do not specifically disclose changing the SNR target value. Dohi teaches changing the SNR target value (see col. 4 lines 20-45). It would have been obvious to one of ordinary skill in the art at the time the invention was made to modify the invention of Kanai and

Art Unit: 2684

Minde, and change the SNR target value, as taught by Dohi, thus allowing accurate system capacity in quickly changing environments, as discussed by Dohi, (col. 2 lines 19-40).

***Allowable Subject Matter***

6. Claims 9 and 16 objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

7. Claims 34-37 are allowed.

***Conclusion***

8. **THIS ACTION IS MADE FINAL.** Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the mailing date of this final action.

9. Any inquiry concerning this communication should be directed to Nick Corsaro at telephone number (703) 306-5616.

Art Unit: 2684

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Nay Maung, can be reached at (703) 308-7745. Any response to this action should be mailed to:

Commissioner of Patents and Trademarks

Washington, D.C. 20231

Or faxed to:

(703) 872-9314 (for Technology center 2600 only)

Hand-delivered responses should be brought to Crystal Park II, 2121 Crystal Drive, Arlington, VA, Sixth, Floor (Receptionist). Any inquiry of a general nature or relating to the status of this application or proceeding should be directed to the Technology Center 2600 customer Service Office whose telephone number is (703) 306-0377.



Nick Corsaro

Primary Examiner

**NICK CORSARO  
PATENT EXAMINER**